
ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00680	Connector, 4 pin M8 A-code plug, 8x19.2 mm, gold plated, molding style, solder cup, IP67, shielded	2	
2	30-01579	Wire, 4C TS, 24 AWG, UL20387, 300V, 105C, 60C oil, UV, 5.5 mm, shielded, VW-1, PVC, 80A, black	1	
3	24-00378	Overmold, M8 plug and jack, 180°	2	PVC, black



Notes:

Cable rated for 30 V, 3 A
Temperature: -40 ~ 105 °C
Oil resistant up to 60 °C
Water resistant up to 75 °C UV resistant

IP67 waterproof rating when mated with corresponding (IP67) connector

Functionally equivalent components may be substituted

50-00680	Wiring Diagram wire color	50-00680			
1	red	1			
2	yellow	2			
3	black	3			
4	white	4			
Shell	shield	Shell			

Revision:	Date:	Description:	Prepared:	Notes:				
Α	3/4/2022	Initial release		RoHS compliant	TENSILITY			
			Verified: Dimensions are in	Function test: no open, no shor intermittent	t circuit, no	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
			millimeters. Tolerances: X: ± 0.5 mm	erances: ± 0.5 mm : ± 0.3 mm Cable, 3000mm, 1.0 mm 4C 50-00680 M8 plug to same, 24 AWG, 30-01579 wire, shielded		Size: Part number: A 10-04164		
			X.X: ± 0.3 mm X.XX: ± 0.05 mm			Scale:	1:1	Sheet 1 of 1
	•	5	4	3	2	•		1