


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-01034	Connector, 6 pin M8 A-code socket, 8x15 mm, gold plated, molding style, solder cup, IP67	1	
2	50-01007	Connector, 6 pin M8 A-code plug, 8x20.3 mm, gold plated, molding style, solder cup, IP67	1	
3	30-02981	Wire, 6C TS, 26 AWG, UL20387, 300V, 105C, 60C oil, UV, 5.6 mm, VW-1, PVC, 80A, black	1	
4	24-00400	Overmold, M8 plug and jack, 180°	2	PVC, black



**Notes:**  
 Cable rated for 30 V, 1 A  
 Temperature: -40 ~ 105 °C  
 Oil resistant up to 60 °C  
 Water resistant up to 75 °C  
 UV resistant

IP67 waterproof rating when mated with corresponding (IP67) connector

Functionally equivalent components may be substituted

Wiring Diagram		
50-01034	wire color	50-01007
1	brown	1
2	white	2
3	blue	3
4	black	4
5	gray	5
6	pink	6

Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant	<b>TENSILITY</b> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	3/13/2023	Initial release	Verified:		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	Size: Part number:
				Cable, 3000mm, 0.7 mm 6C 50-01034 M8 socket to 0.7 mm 50-01007 M8 plug, 26 AWG, 30-02981 wire	A 10-05440
				Scale: 1:1	Sheet 1 of 1

5

4

3

2

1