


Specifications:

connector description (1)	dc plug, 3.2x0.9xL20.2 mm, spring contacts, 3 conductors, P/N 50-00074
overmold (2)	30P, PVC, black
wire description (3)	3C, 24 AWG, 300V, 80C, 3.4 mm, PVC, 65P, P/N 30-00006
cable outer diameter	Ø3.4 mm
cable color	black
cable gauge	AWG #24
cable length	1830 ± 50 mm
twist tie (4)	black, 89 ± 3


Notes:

Function test: no open, no reversed polarity, no short circuit, no INT
 RoHS compliant

Mechanical drawing:



Wiring diagram:



Initial

Date

tolerance X: ±0.5 mm .X: ±0.3 mm .XX: ±0.05 mm
 applicable unless otherwise indicated in specification or on drawings

Revision notes:

Rev	Date	Description
A	March 29, 2010	Re-issue. Original specification issued by CUI Inc; re-issued by Tensility without any material or mechanical changes.
A1	May 5, 2010	includes additional plug and wiring diagram detail
A2	August 31, 2011	updated description, connector, and wire information

Specification Approval

Spec sign-off verifies that you have reviewed the entire specification, tested a sample of the product, and confirm that it meets your requirements. This specification reflects the part as it will be ordered. Orders will not be processed until the specification pages have been initialed and the approval page has been signed. This specification is confidential and is not to be transmitted without prior approval from Tensility.

Signature _____

Title _____

Name _____

Date _____

Company _____

Branch _____